

Стандартные кабельные ручные фонари

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	

ELECTRONIC LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	2.00
Luminous flux [lm]*:	200
Colour temperature [K]:	4000
Ingress protection:	IP20
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Colour rendering index:	>80
Material of the body:	Polietylen
Dimensions (H/W/T/S) [mm]:	375/37
Warranty [years]:	2

CHARACTERISTICS

- Power: 2W
- Luminous flux: 200lm
- Light source: SMD LED
- Handle and cap made of polythene
- Diffuser made of PVC
- Rotating hook
- Weight: 0,4 kg
- Cable H05VV-F 2x0,75 mm (5m)

APPLICATION

ELECTRONIC LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Plug type	Dimensions (H/W/T/S) [mm]	Index
2	200	Universal	375/37	>> 271038

PROFI SMD LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	4.00; 5.00
Luminous flux [lm]*:	450; 700
Colour temperature [K]:	4000
Ingress protection:	IP54
Supply voltage [V]:	12; 220 - 240; 24
Frequency [Hz]:	50 - 60
Electrical protection class:	II; III
Colour rendering index:	>80
Material of the body:	gum
Dimensions (H/W/T/S) [mm]:	60/415
Warranty [years]:	2

CHARACTERISTICS

- Power: 4W, 5W
- Luminous flux: 450lm, 700lm
- 65% less power consumption (compared to Profi 11W)
- Light source: SMD LED
- Polycarbonate impact-resistant prismatic diffuser
- Handle and cap made of rubber
- High ingress protection class IP54
- Rotating hook
- Weight: 0,7 kg
- Rubber cable H05RN-F 2x1 mm² (5m)
- Spare parts available

APPLICATION

PROFI SMD LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	450	UNI-SCHUKO	60/415	>> 260834
5	700	CAR	60/415	>> 380976
5	700	CEE	60/415	>> 380983
5	700	TRAFO	60/415	>> 380990

PROFI 36W

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	36.00
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]*:	1200
Electrical protection class:	II
Diffuser material:	PC
Diffuser type:	transparent
Material of the body:	gum
Colour of the body:	black
Working temperature [°C]:	from -20 to +35
Dimensions (H/W/T/S) [mm]:	1460/60
Warranty [years]:	2

CHARACTERISTICS

- Power: 36W
- Luminous flux: 1200lm
- 85% lower power consumption (compared to 250W incandescent source)
- Light source: energy saving fluorescent tube T8 (G13)
- Polycarbonate prismatic diffuser
- Handle and cap made of rubber
- Rotating hook
- Weight: 1,3 kg
- Rubber cable H05RN-F 2x1 mm² 5m
- Movable assembly panel to facilitate light source replacement
- Spare parts available

APPLICATION

PROFI 36W

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Working temperature [°C]	Dimensions (H/W/T/S) [mm]	Index
36	1200	from -20 to +35	1460/60	>> 892165

EFFECT LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	4.00
Luminous flux [lm]*:	400
Colour temperature [K]:	4000
Ingress protection:	IP20
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Colour rendering index:	>80
Material of the body:	PP
Dimensions (H/W/T/S) [mm]:	390/50
Warranty [years]:	2

CHARACTERISTICS

- Power: 4W
- Luminous flux: 400lm
- Light source: SMD LED
- Casing made of polypropylene
- Diffuser made of impact-resistant polycarbonate
- Rotating hook
- Weight: 0,5 kg
- Cable H05VV-F 2x0,75 mm² (5m)

APPLICATION

EFFECT LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	400	Universal	390/50	>> 270109



HOBBY LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	4.00
Luminous flux [lm]*:	400
Colour temperature [K]:	4000
Ingress protection:	IP20
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	II
Colour rendering index:	>80
Material of the body:	PP
Dimensions (H/W/T/S) [mm]:	390/50
Warranty [years]:	2

CHARACTERISTICS

- Power: 4W
- Luminous flux: 400lm
- Light source: SMD LED
- Casing made of polypropylene
- Diffuser made of impact-resistant polycarbonate
- Rotating hook
- Weight: 0,5 kg
- Cable H05VV-F 2x0,75 mm² (5m)

APPLICATION

HOBBY LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	400	UNI-SCHUKO	390/50	>> 111280

OPTIM LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	2.00
Luminous flux [lm]*:	230
Supply voltage [V]:	220 - 240
Electrical protection class:	II
Light colour:	biały
Diffuser material:	PVC
Diffuser type:	transparent
Material of the body:	PP
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	380/36

CHARACTERISTICS

- Light source: SMD LED
- Luminous flux: 230lm
- Power: 2W
- Ingress protection class: IP20
- Cover made with PCV
- Lamp elements made with PP
- Retractable rotating hook
- Weight: 0,4 kg
- Cable: 5m H05W-F 2x0,75m2

APPLICATION

OPTIM LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
2	230	black	380/36	>> 205958

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Россия (495)268-04-70

Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Киргизия (996)312-96-26-47

Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Казахстан (7172)727-132

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93