

Стандартные портативные светодиодные лампы АССУ

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	

HANDY FUTURE LED

GENERAL CARD



HANDY FUTURE LED

GENERAL CARD

TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	3.00
Colour temperature [K]:	6500
Ingress protection:	IP20
Diffuser colour:	transparent
Material of the body:	TPR
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	155/40/20

CHARACTERISTICS

The manual LED luminaire is a proposal for people working in a car workshop, mobile service center, garage, or on a construction site. Professionals and DIY enthusiasts alike will benefit from the functionality of the LED hand-held luminaire - everyone for whom good lighting is important during work or hobby. The luminaire is characterized by high durability, a strong light beam, and a long working time, which allows you to focus on the task. At the same time, the emitted light is pleasant to the eyes, and the energy-saving LED technology itself.

- Light source: 3 W COB LED + 3 W LED
- Luminous flux: 60 and 150 lm
- Strong magnet in the base
- Durable casing
- Dimensions: 155x40x20 mm
- 2 lighting modes
- Ingress protection class: IP20
- Rotatable hook
- Charging time: 3,5 h
- Lighting time: 2,5 h
- Indicator of the battery charging state

APPLICATION

It is used as a working luminaire for lighting workplaces, workshops, or garages.

HANDY FUTURE LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Battery	Battery capacity [mAh]	Material of the body	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
3	6500	3.7V 18650 1200mAh	1200	TPR	green	155/40/20	>> 608551

HANDY MULTI LED

GENERAL CARD



HANDY MULTI LED

GENERAL CARD

TECHNICAL PARAMETERS

Light source:	LED
Ingress protection:	IP40
Rated power of the luminaire [W]*:	5.00
Colour temperature [K]:	6500
Diffuser colour:	transparent
Material of the body:	PC + TPR + Aluminium
Colour of the body:	green
Dimensions (H/W/T/S) [mm]:	150/48/39

CHARACTERISTICS

The manual LED luminaire is a proposal for people working in a car workshop, mobile service center, garage, or on a construction site. Professionals and DIY enthusiasts alike will benefit from the functionality of the LED hand-held luminaire - everyone for whom good lighting is important during work or hobby. The luminaire is characterized by high durability, a strong light beam, and a long working time, which allows you to focus on the task. At the same time, the emitted light is pleasant to the eyes, and the energy-saving LED technology itself.

- Light source: 5 W COB LED + 2 x 3 W LED
- Luminous flux: 240 and 400 lm
- Strong magnet in the base
- Durable casing
- Dimensions: 150x48x39 mm
- 2 lighting modes
- Ingress protection class: IP40
- Charging time: 3,5 h
- Lighting time: 2,5 - 4 h
- Stepless dimming and brightening

APPLICATION

It is used as a working luminaire for lighting workplaces, workshops, or garages.

HANDY MULTI LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Rated power of the luminaire [W]*	Colour temperature [K]	Battery	Battery capacity [mAh]	Diffuser colour	Material of the body	Colour of the body	Dimensions (H/W/T/S) [mm]	Index
5	6500	Li-ion 3,7V 18650 2000mAh	2000	transparent	PC + TPR + Aluminium	green	150/48/39	>> 608568

STOF COB LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP20
Supply voltage [V]:	3.7
Electrical protection class:	III
Colour rendering index:	>80
Charging time [h:min]:	4
Battery life [h:min]:	4
Battery:	Li-Ion
Dimensions (H/W/T/S) [mm]:	240/58
Warranty [years]:	2

CHARACTERISTICS

- Light Source: SMD LED
- Polycarbonate prismatic diffuser
- 3 magnets included
- Rotating hook
- Li-Ion 3.7V 2200mAh battery
- Charging time: 4 h
- Working time: 4 h
- Charger : AC110-240V/DC 12 V; 5V500mA
- Weight: 0,2 h
- Charger, car charger included

APPLICATION

STOF COB LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Charging time [h:min]	Battery life [h:min]	Battery	Battery capacity [mAh]	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	4	Li-Ion	2200	Universal	240/58	>> 334436

DRAGO SMD LED

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	2.00
Luminous flux [lm]*:	220
Colour temperature [K]:	6500
Ingress protection:	IP54
Supply voltage [V]:	3.7
Frequency [Hz]:	50 - 60
Electrical protection class:	III
Colour rendering index:	>80
Charging time [h:min]:	4.00
Battery life [h:min]:	4.00
Battery:	Li-Ion
Dimensions (H/W/T/S) [mm]:	125/65/35
Warranty [years]:	2

CHARACTERISTICS

- Light source: 2W COB LED
- Luminous flux 220lm (option high), 100lm (high option)
- Strong magnet in base
- Torchlight function
- Protection class: III
- Retractable rotating hook in handle
- Charger in set: USB 100-240 AC/DC 5V1A + 1,5m micro
- Weight: 0,175 kg
- Li-Ion 3,7V 2200mAh battery
- Charging time: 4h
- Working time: 4h
- Multi-positional arm +/- 180°

APPLICATION

DRAGO SMD LED

GENERAL CARD

AVAILABLE VERSIONS




Click index >>, to see details

Nominal power [W]	Luminous flux [lm]*	Charging time [h:min]	Battery life [h:min]	Battery	Battery capacity [mAh]	Plug type	Dimensions (H/W/T/S) [mm]	Index
2	220	4.00	4.00	Li-Ion	1500	Universal	125/65/35	>> 334566

FUTURE FLEX LED

OPRAWY RĘCZNE DIODOWE / HAND LED LAMPS



w komplecie: / included:



możliwości: / capabilities:



LED | IK10 | IP65 | 220-240V
50-60Hz | III | CE | T



- Źródło światła SMD LED
- Tryby działania przy pracy akumulatorowej:
 - +400lm, czas pracy 2h
 - +200lm, czas pracy 4h
 - +100lm, czas pracy 8h
 - +100lm, czas pracy 8h (źródło czołowe)
- Kąt świecenia 60° / 45°
- Elastyczny przegub 360°
- Bardzo wysoki stopień szczelności: IP65
- Klosz transparentny wykonany z poliwęglanu
- Obudowa z poliwęglanu powlekanego gumą
- Chowany, obrotowy wieszak w ręczce
- 3 neodymowe magnesy w podstawie
- Wyłącznik typu tact-switch: kolejne użycia uruchamiają następujące po sobie tryby świecenia.
- Akumulator Li-Ion 3,7V 2200mAh
- Czas ładowania: 2,5h
- Zasilacz µUSB 230V / 5V 1000mA (w opcji)
- Wskaźnik ładowania akumulatora
- Waga 0,3kg
- Możliwość dokupienia i wymiany podzespołów

- Light source: SMD LED
- ACCU mode working types:
 - +400lm, 2h working time
 - +200lm, 4h working time
 - +100lm, 8h working time
 - +100lm, working time 8h (ftop part)
- Lighting angle 60° / 45°
- Elastic joint 360°
- High ingress protection class: IP65
- Polycarbonate prismatic diffuser
- Casing made of polycarbonate covered with rubber
- Retractable rotating hook in handle
- 3 neodymium magnets in base
- On/off switch type tact-switch: the first use turn on front part, a second use main part
- Li-Ion 3,7V 2200mAh battery
- Charging time: 2,5h
- Charger µUSB 230V / 5V 1000mA (optional)
- Indicator of battery state
- Weight 0,3kg
- Spare parts available

index	nazwa article	kl.ochronności protection class
246982	FUTURE FLEX LED with µUSB charger / z zasilaczem µUSB	III
246999	FUTURE FLEX LED	III

EYE COB LED

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Supply voltage [V]:	3.7
Electrical protection class:	III
Colour rendering index:	>80
Charging time [h:min]:	4
Battery life [h:min]:	5/2.5
Battery:	Li-Ion
Material of the body:	rubberized
Dimensions (H/W/T/S) [mm]:	266/41
Warranty [years]:	2

CHARACTERISTICS

- Light source: COB LED
- ACCU mode working types:
 - 500lm, 2,5h working time
 - 250lm, 5h working time
 - 100lm, working time 10h (top part)
- Elastic joint +/- 180° +/- 180° (Horizontally), +/- 120° (Vertically)
- Strong magnet in the base
- Protection class: III
- Retractable rotating hook in the handle
- Charger in set: USB 100-240 AC/DC 5V1A + 1,5m micro
- Dimensions: 52x41.5x266mm
- Weight: 0,33 kg
- Li-Ion 3,7V 2600mAh battery
- Lamp covered with rubber
- Charging time: 4H
- Working time: 5H/2,5H
- Indicator of battery state
- A three-level battery level indicator

APPLICATION

EYE COB LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Charging time [h:min]	Battery life [h:min]	Battery	Battery capacity [mAh]	Plug type	Dimensions (H/W/T/S) [mm]	Index
4	5/2.5	Li-Ion	2600	Universal	266/41	>> 334641

DIUNA COB LED

GENERAL CARD



TECHNICAL PARAMETERS

Luminous flux [lm]*:	200
Ingress protection:	IP40
Supply voltage [V]:	3.7
Electrical protection class:	III
Colour rendering index:	>80
Charging time [h:min]:	4
Battery life [h:min]:	5
Battery:	Li-Ion
Material of the body:	rubberized
Dimensions (H/W/T/S) [mm]:	160/49
Warranty [years]:	2

CHARACTERISTICS

- Light source: COB LED
- Luminous flux: 200lm
- Strong magnet in the base
- Protection class: III
- Retractable rotating hook
- Dimensions: 160x49x37mm
- Weight: 0,2 kg
- Li-Ion 3,7V 2200mAh battery
- Lamp covered with rubber
- Charging time: 4H
- Working time: 5H
- Battery level indicator

APPLICATION

DIUNA COB LED

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Luminous flux [lm]*	Charging time [h:min]	Battery life [h:min]	Battery	Battery capacity [mAh]	Plug type	Dimensions (H/W/T/S) [mm]	Index
200	4	5	Li-Ion	2200	Universal	160/49	>> 334665

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	