

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	

UV-C STERILON 36W

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	36.00
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	215/320/95
Ingress protection:	IP20
Mounting version:	mounting on a tripod or wall bracket
Warranty [years]:	2

CHARACTERISTICS

UV-C STERILON 36W lamps emitting ultraviolet light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is enough to direct the UV lamp directly onto the surface for a specified time to effectively kill microorganisms. They are so powerful that they may produce harmful effects on human skin or eyes. Therefore, basic safety precautions should be observed when using UVC lamps for disinfection, i.e. you should not stay within the range of the light beam.


APPLICATION

Lamps with power 36W will disinfect a space of about 15m². There are recommended for use in healthcare facilities, grocery stores, public and private means of transport, at petrol stations, in courier companies, public administration, and educational establishments. Depending on the distance from the light source, temperature and humidity, we take 15 minutes as an approximate disinfection time.

UV-C STERILON 36W

GENERAL CARD

AVAILABLE VERSIONS

 Click index >>, to see details

Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Net weight of the luminaire [kg]	Index
36	9000	UNI- SCHUKO	5	I	220 - 240	1.380	>> 243943

UV-C STERILON 36W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
000720	Standard tripod
243615	Magnetic holder UV-C Sterilon 36W
243622	Ceiling holder UV-C Sterilon 180x180x12mm
243639	UV-C protective glasses
160UV003	TC-L UV-C 18W 2G11 TUV fluorescent lamp



Standard tripod (000720)



UV-C protective glasses (243639)

UV-C STERILON RCR 36W

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	36.00
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	215/320/95
Ingress protection:	IP20
Mounting version:	mounting on a tripod or wall bracket
Warranty [years]:	2

CHARACTERISTICS

UV-C STERILON lamps emitting ultraviolet light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is enough to direct the UV lamp directly onto the surface for a specified time to effectively kill microorganisms. They are so powerful that they may produce harmful effects on human skin or eyes. Therefore, basic safety precautions should be observed when using UVC lamps for disinfection, i.e. you should not stay within the range of the light beam. **The task of the inverted RCR motion sensor** is to protect people and animals against accidental intrusion into the zone of direct UV-C radiation of the lamp when it is switched on. When motion is detected (contrary to the standard application of the RCR sensor), the UV-C module is turned off. If there is no motion for a period of 10 minutes (in the specified coverage zone), the UV-C module is turned on again.


APPLICATION

Lamps with power 36W will disinfect a space of about 15m². There are recommended for use in healthcare facilities, grocery stores, public and private means of transport, at petrol stations, courier companies, public administration, and educational establishments. Depending on the distance from the light source, temperature and humidity, we take 15 minutes as an approximate disinfection time.

UV-C STERILON RCR 36W

GENERAL CARD

AVAILABLE VERSIONS

 Click index >>, to see details

Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Net weight of the luminaire [kg]	Index
36	9000	UNI- SCHUKO	5	I	220 - 240	1.520	>> 240386

UV-C STERILON RCR 36W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
000720	Standard tripod
243615	Magnetic holder UV-C Sterilon 36W
243622	Ceiling holder UV-C Sterilon 180x180x12mm
WSEL433	RCR remote control / programmer
243639	UV-C protective glasses
160UV003	TC-L UV-C 18W 2G11 TUV fluorescent lamp



Standard tripod (000720)



UV-C protective glasses (243639)

UV-C STERILON 72W/108W

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	72.00; 108.00
Supply voltage [V]:	220 - 240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	270/480/100
Ingress protection:	IP20
Mounting version:	mounting on a tripod or wall bracket
Warranty [years]:	2

CHARACTERISTICS

UV-C lamps emitting ultraviolet light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is enough to direct the UV lamp directly onto the surface for a specified time to effectively kill microorganisms. They are so powerful that they may produce harmful effects on human skin or eyes. Therefore, basic safety precautions should be observed when using UVC lamps for disinfection, i.e. you should not stay within the range of the light beam.

APPLICATION

Lamps with higher power (108W) will prove well in a room up to 35m², those with the wattage of 72W are designed for areas of up to 25m². There are recommended for use in healthcare facilities, grocery stores, public and private means of transport, at petrol stations, courier companies, public administration, and educational establishments. Depending on the distance from the light source, temperature and humidity, we take 15 minutes as an approximate disinfection time.

UV-C STERILON 72W/108W

GENERAL CARD

AVAILABLE VERSIONS



Click index >>, to see details

Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Net weight of the luminaire [kg]	Index
108	9000	UNI- SCHUKO	5	I	220 - 240	3.200	>> 243967
72	9000	UNI- SCHUKO	5	I	220 - 240	2.760	>> 243905

UV-C STERILON 72W/108W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
243615	Magnetic holder UV-C Sterilon 36W
243622	Ceiling holder UV-C Sterilon 180x180x12mm
243639	UV-C protective glasses



FUTURE STAND Tripod with Click Head System (000737)



UV-C protective glasses (243639)

UV-C STERILON RCR 72W/108W

GENERAL CARD



TECHNICAL PARAMETERS

Nominal power [W]:	72.00; 108.00
Supply voltage [V]:	220 - 240
Electrical protection class:	I; II
Material of the body:	PP
Colour of the body:	white; white body
Dimensions (H/W/T/S) [mm]:	270/480/100
Ingress protection:	IP20
Mounting version:	mounting on a tripod or wall bracket
Warranty [years]:	2

CHARACTERISTICS

UV-C STERILON lamps emitting ultraviolet light are one of the most effective devices capable of removing viruses, bacteria, fungi from the surface or destroying the DNA or RNA of any exposed microorganisms. It is enough to direct the UV lamp directly onto the surface for a specified time to effectively kill microorganisms. They are so powerful that they may produce harmful effects on human skin or eyes. Therefore, basic safety precautions should be observed when using UVC lamps for disinfection, i.e. you should not stay within the range of the light beam. **The task of the inverted RCR motion sensor** is to protect people and animals against accidental intrusion into the zone of direct UV-C radiation of the lamp when it is switched on. When motion is detected (contrary to the standard application of the RCR sensor), the UV-C module is turned off. If there is no motion for a period of 10 minutes (in the specified coverage zone), the UV-C module is turned on again.


APPLICATION

Lamps with higher power (108W) will prove well in a room up to 35m², those with the wattage of 72W are designed for areas of up to 25m². There are recommended for use in healthcare facilities, grocery stores, public and private means of transport, at petrol stations, courier companies, public administration, and educational establishments. Depending on the distance from the light source, temperature and humidity, we take 15 minutes as an approximate disinfection time.

UV-C STERILON RCR 72W/108W

GENERAL CARD

AVAILABLE VERSIONS

 Click index >>, to see details

Nominal power [W]	Service life of the UV-C radiation source [h]	Plug type	Cable length [m]	Electrical protection class	Supply voltage [V]	Net weight of the luminaire [kg]	Index
72	9000	UNI- SCHUKO	5	I	220 - 240	3.100	>> 240362
108	9000	UNI- SCHUKO	5	II	220 - 240	3.800	>> 240379

UV-C STERILON RCR 72W/108W

GENERAL CARD

ACCESSORIES AVAILABLE

index	Name
000737	FUTURE STAND Tripod with Click Head System
WL36500	PL-L UV-C 36W 2G11 OSR fluorescent lamp
243615	Magnetic holder UV-C Sterilon 36W
243622	Ceiling holder UV-C Sterilon 180x180x12mm
WSEL433	RCR remote control / programmer
243639	UV-C protective glasses



FUTURE STAND Tripod with Click Head System (000737)



UV-C protective glasses (243639)

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	